

 **LM TRAC**

**286**



› LM Trac 286

## Technical data

# 286



### ENGINE AND TRANSMISSION

Engine	Lombardini LDW1603 CHD Plus, 3-cyl. diesel
Cylinder capacity	1649 cm <sup>3</sup>
Power	27 kW / 2400 rpm (36 hp)
Torque	113 Nm / 1600 rpm
Transmission	Continuous hydrostatic 2-wheel or 4-wheel drive

### DRIVE HYDRAULICS

Output	0-60 ltr/min / 2400 rpm (drive pump)
Pressure	350 bar (drive pump)
Speed ranges	0-15 km/h & 0-30 km/h (2WD) 0-6.5 km/h & 0-13 km/h (4WD)
Forward/reverse selection	Drive pedal
Steering	Hydrostatic rear wheel steering (LS)
Brakes	Hydrostatic, wet disc brakes front, electric parking brake
Tires	31 x 11.5 R15 front, 175 / 13 rear
Fuel tank	35 ltr

### WORK HYDRAULICS

Type	Fixed displacement, open system
Engine hydraulics	47 ltr/min / 2400 rpm
Pressure MAX	200 bar

### CYLINDER HYDRAULICS

Output	15 ltr/min / 175 bar
Control	Two Mini-Joysticks
Implement connection	A-frame
Hydraulic oil tank	55 ltr
Electrical system	12 V

### OPTIONAL EQUIPMENT

Air-conditioning, Air seat, LED work lights, Radio/CD player, Cabin heating, Rear hydraulics, Hitch, etc.

### DIMENSIONS AND WEIGHT

Length	2680 mm
Height	2095 mm
Width	1340 mm
Turning radius, inner	1025 mm
Ground clearance	180 mm
Dead weight	1140 kg

We reserve the right to modifications without prior notice.

MANUFACTURER:



OY LAI-MU AB  
NIITTAJANTIE 9  
FI-26820 RAUMA

TEL: +358 2 8387 2400  
FAX: +358 2 8387 2444

www.laimu.fi  
laimu@laimu.fi

DISTRIBUTOR:

LM TOOLS

LM Tools for all needs.